

## **DYNAMIC PREDICTIVE RESOURCE RESERVATION IN WIRELESS NETWORKS**

### **FIELD OF THE INVENTION**

This invention generally relates to provision of services in mobile wireless

5 Internet Protocol (IP) networks and more specifically relates to allowing mobility of service for subscribers in such wireless networks.

### **BACKGROUND**

Two recent technological hallmarks have been the development of the personal computer and the wireless mobile telephone or cellular phone. In fact, the  
10 last ten years of the twentieth century has been marked by unprecedented growth in the demand for personal computers, particularly laptops, and wireless telephones (or cell phones). The personal computer owes its popularity mainly in part to its ability to access and process relatively large amounts of data, its price, and its size, especially in the case of laptops. Specifically, a personal computer allows for accessing and  
15 processing large amounts of multimedia information available, for example, via the Internet from the top of a desk or the lap of a user. Consumers via the Internet can access, send, and receive email messages, preview movies, research intended purchases, etc. In essence the Internet and personal computer have made the consumer smarter through access to a heretofore unimaginable plethora of  
20 information.

Cell phones, on the other hand, have allowed users mobility previously unavailable by wireline phones. Specifically, whereas a wireline phone restricts the user's mobility to the location of the phone, a user may make and receive calls from a cell phone even while roaming over a very large geographical area such as the

contiguous United States. In addition, as the user roams geographically the quality of service is maintained at a fairly high level.

Merging the mobility of the cellular network with the information capability and accessibility of the Internet has become a main focus of the communications industry. In particular, in recent years considerable research has been directed to developing mobile protocols that would allow seamless access to the multimedia services available on the Internet anytime and anywhere.

The Internet is a packet data network in which the Internet Protocol (IP) defines the manner in which a user is connected to the Internet so as to access, transmit, and receive information from other users or resources connected to the Internet. In particular, in accordance with IP each network access point is identified by an IP address. When a user attaches to a particular network access point the user, more precisely, the user's terminal, is given an IP address. The addresses available at access point are assigned geographically. Consequently, as a user roams geographically the user's point of attachment to the network changes which in turn requires the user's IP address to change. Further, information destined for a user, or resource, is packetized with each packet having the IP address of the user, more accurately the user's terminal, in a header. As packets traverse the network, the IP address included in the header is used to route the packet to its destination. Thus, as a user roams and her IP address changes the route of the packet changes, which in turn may affect the quality of service for some multimedia services, i.e., real time services, as there is no guarantee that network resources required to support the service are available. At a fundamental level IP was not designed with mobility in mind as evidenced by the manner in which IP addresses are assigned.

In contrast, the wireless telephone network is a circuit switched network with each user's telephone number serving as a unique access identifier. Consequently, as the user roams geographically the user's identity is unchanged thereby allowing the network to easily track the user's movement, establish new circuits in anticipation of the user moving to a different geographic region, and maintain the needed quality of service. In addition, in the wireless telephone network calls between users are routed through the network on circuits that are established for the duration of the call. In other words, a path is established in the network for exclusively carrying each call thereby assuring the user of the bandwidth needed for the service.

Given the fundamentally different approaches underlying the manner in which access is provided to the Internet and to the wireless telephone network and the manner in which paths are established and signals routed through each of these networks, many issues need to be resolved before multimedia services can be provided over a wireless IP network. Nonetheless, forecasts indicate that users or consumers will ultimately desire accessing currently available and future multimedia services available via the Internet while being mobile, i.e., combining the cell phone mobility with the processing power of the personal computer. As such, there has been an international effort to provide mobile access to Internet protocols.

Responding to this apparent demand, the International Telecommunications Union (ITU) promulgated International Mobile Telecommunications - 2000 (IMT-2000) global standards to allow for wireless access to multimedia information or services available via the Internet in much the same way consumers are use to using their cell phones, so called third generation wireless (3G wireless) services. The IMT-2000 standards have made significant progress in defining a common radio system architecture, including services, interfaces, and radio spectra. For example,

at the physical layer, IMT-2000 includes standards on the frequency of the chip sets used to support the services and the radio frequency spectrum, which will be used for the services. By physical layer we refer to the first layer of the 7-layer Open System Interconnect (OSI) reference model wherein the layers are ordered as follows: layer 1 is the physical layer and the lowest layer in the stack, layer 2 is the link layer and above layer 1, layer 3 is the network layer and above layer 2, layer 4 is the transport layer and above layer 3, layer 5 is the session layer and above layer 4, layer 6 is the presentation layer and above layer 5, and layer 7 is the applications layer and the highest layer. IMT-2000 includes definitions on upper layer protocols, but mostly for circuit based networks. IMT-2000 also includes standards on Time Division Multiple Access (TDMA) and Code Division Multiple Access (CDMA) technologies.

The ITM-2000 standard has spawned numerous industry organizations and groups all with the general goal of developing applicable technical specifications for supporting CDMA 2000, W-CDMA, and third generation TDMA systems. Some of these organizations include the 3<sup>rd</sup> Generation Partnership Project (3GPP), the 3<sup>rd</sup> Generation Partnership Project 2 (3GPP2) and the Mobile Wireless Internet Forum (MWIF). These organizations are directing their efforts to solving the problems that will be encountered in trying to provide 3G wireless multimedia services or mobile access to Internet services.

In a conventional prior art wireless network such as shown in FIG. 1A, a plurality of base stations 10 transmit or send information over the air to a plurality of mobile units 20. The range within which a mobile unit 20 can reliably receive information from a base station 10 defines a cell 21. As illustrated in FIG. 1A the cells 21 may be depicted as a honeycomb structure. As a mobile unit 20<sub>2</sub>, for

example, roams and moves further away from a base station  $10_2$  corresponding to cell  $21_2$  for base station  $10_2$ , signal strength decreases. Further, as the mobile moves from one cell to another, the mobile station needs to switch from its serving base station, the base station for the cell it currently is in, to a target base station, the base station for the cell that it's moving to. The process of the mobile switching base stations is known as handoff.

Handoff can be hard or soft. In a hard handoff a user may receive data from only one base station at any given time. In other words, there is a single wireless data transport path for a user at any given time and the path has to change when the user moves from one cell to another. This could cause data in transit, e.g., data that has been sent to the previous serving base station, to be lost during hard handoff therefore causing performance degradation.

In a soft handoff, the user seamlessly switches from one base station to the next without any perceptible degradation in service. During a soft handoff a mobile user communicates with multiple base stations simultaneously. Therefore, a user may be able to switch to a new base station without data loss. Soft handoff is the method of choice employed in the conventional CDMA wireless network. In addition, soft handoff must be supported in 3G wireless networks, as it would be awfully inconvenient for a user's service, e.g., a video conference, to be disrupted each time the user switches base stations.

In addition to providing for seamless service, soft handoff also allows cells to cover a larger geographic area. This is the case because during soft handoff the mobile unit receives signals from at least two base stations and combines these received signals to obtain the information intended for the user. Because it receives two or more signals, each signal can be at a lower level than if the mobile were

receiving only one signal. Accordingly, each base can be allowed to cover a larger geographic area.

The network of FIG. 1B is currently able to support cellular telephony and limited data transmissions, e.g., 9.6 kb/s for GSM and 14.4 kb/s for CDMA, and is usually referred to as 2G wireless network. With reference to FIG. 1B we will illustrate how soft handoff occurs in today's network. A user's mobile unit 20 is communicating with its serving base station 10<sub>5</sub> in the corresponding cell 21<sub>5</sub>. The base station 10<sub>5</sub>, and probably mobile 20, monitor the signal strength of the mobile unit 20 and when the mobile's signal strength drops below a pre-specified level soft handoff is initiated. That is, as the mobile enters the soft handoff region 33, the base station 10<sub>5</sub> and the mobile unit 20 together initiate the appropriate steps through a base station controller 35 and a mobile switching center 40, if necessary, in circuit switched network 47 to locate the target base station 10<sub>6</sub> for the neighboring cell 21<sub>6</sub> serving the same soft handoff region 33. Note that the mobile switching center would not be included in soft handoff, given the current illustrative example, because both base stations are controlled by the same base station controller. Identical information intended for the mobile unit 20 is then routed to both the target base station 10<sub>5</sub> and the serving base station 10<sub>6</sub>. Both base stations in turn transmit the identical information to mobile unit 20. The mobile unit 20 then combines the signal to produce the information intended for the user. As the mobile unit 20 leaves the soft handoff region 33 and enters the target cell 21<sub>6</sub>, soft handoff is terminated and the target base station 10<sub>6</sub> becomes the only base station serving the mobile unit 20. In a similar manner the mobile unit is handed from base station to base station as the unit roams from cell to cell.

Ultimately the network architecture of FIG. 1B will transition to the IP-based autonomous wireless base stations network of FIG. 1C. In comparing the architecture of FIG. 1C to FIG. 1B, we note the following important differentiating features of FIG. 1C: (1) base stations 100 function autonomously, i.e., there are no base station controllers or mobile switching centers to centrally control the base stations; (2) the backbone network 107, including connections 117 that interconnects the base stations 100 is an all IP network, as opposed to a circuit switched network; and (3) the base stations are capable of performing IP layer processing, e.g., forwarding packets based on information in the IP headers, signaling, and mobility management.

Of particular import to the present invention is the reservation of resources needed within a wireless network during handoff. In order for handoffs to occur the target or new cell must have enough resources, e.g., radio channels, radio channel capacity, bandwidth, IP addresses (if mobile units in the new and previous cells use disjoint sets of IP addresses), etc., available to accept, at some predetermined quality of service level, the entering mobile unit without significantly degrading the quality of service of mobiles or users already supported by the target cell. A mobile call already in progress may be aborted during handoff because the target cell cannot allocate sufficient resources to support the entering mobile. For example, a user on a videoconference in cell 21<sub>5</sub> requires sufficient bandwidth in cell 21<sub>6</sub> to support the videoconference. If cell 21<sub>6</sub> does not have the bandwidth necessary to support the videoconference, then the videoconference will end for this user once he moves beyond reach of his current serving base station 10<sub>5</sub>. Forced termination of an on-going call due to handoff is more undesirable, from a user's perspective, than rejecting a new call. Thus, low handoff blocking probability is a key requirement in

wireless networks. Reserving resources for future handoff calls is an effective way to reduce handoff call blocking probability.

Existing resource management mechanisms for supporting handoff in wireless networks fall into the following categories:

- Non-reservation Mechanisms – A non-reservation mechanism is one in which free resources are assigned if there is at least one call that requests it. In other words, a base station does not reserve any resources for handoffs or handoff calls.
- Reservation-based Mechanisms – A predetermined amount of network resources are set aside for use only by handoff calls.

Reservation-based mechanisms can be divided into two classes. The first class is generally referred to as fixed reservation. With fixed reservation a fixed amount of resources are reserved for handoff calls. The second class is generally referred to as dynamic (adaptive) reservation. With dynamic reservation the amount of resources reserved or available depend on the amount of resources that will be required by handoff calls.

Existing methods for dynamically predicting and reserving resources for future handoff calls can be classified into collaborative and local methods. Collaborative methods require a base station to collaborate with other base stations to make resource reservation decisions. They typically require each base station to gather real-time information on the behaviors of mobile stations in neighboring cells. Such information may include mobility patterns and traffic volumes of mobile stations in neighboring cells, the number of mobile stations or the number of calls in each service class that are expected to be handed off from a neighboring cell. Collecting such information could become difficult when mobile stations' velocities vary widely



and users have access to multimedia services, as expected in IP-based multimedia wireless networks. Frequent exchange of mobile station mobility information among the base stations could increase overall wireless system complexity and overhead, especially in IP-based picocellular networks.

5        A recent method that uses only locally available information to make reservation decisions has been proposed by Luo, X., et. al., in their paper entitled "A Dynamic Pre-Reservation Scheme for Handoffs with GoS Guarantee in Mobile Networks", IEEE International Symposium on Computers and Communications, July 1999 (hereinafter Luo). This method assumes that the arrival process of handoff requests into a cell is a Poisson process, the holding time of each handoff call in 10 each cell is exponentially distributed, and each call require an equal amount of resources. Each base station measures the average rate of arrival handoff requests. It then uses a M/M/1 queuing model to estimate the number of channels required for handoff calls, where the number of required radio channels is modeled as the number of buffers in the queue. Other local methods can also be found in, for 15 example, L. Ortigoza-Guerrero, A. H. Aghvami, "A Prioritized Handoff Dynamic Channel Allocation Strategy for PCS", IEEE Transactions on Vehicular Technology, Vol. 48, Bo. 4, July 1999 and S. Kim, T. F. Znati, "Adaptive Handoff Channel Management Schemes for Cellular Mobile Communication Systems", ICC'99.

20        Existing local methods pose a number of potential problems. First, they can only handle "homogeneous" radio channels, i.e., radio channels with the same allocated capacity. In wireless IP networks that support multiple services (e.g., data, voice, and video), capacity allocated to each radio channel will vary widely depending on the type of service the channel supports or even within a single 25 service type (e.g., channels with different capacities can be used to support different

data services). Second, they assume that handoff and new call arrival processes to be Poisson and stationary in the mean (i.e., the mean is the same over time) and that the handoff call holding time inside each cell to be exponentially distributed. These conditions may not hold in a real wireless network, especially in wireless IP networks that often consist of a large number of very small cells (e.g., picocells). In such networks, handoff becomes more frequent, handoff call arrivals are likely to be non-Poisson and non-stationary for extended periods of time. In fact, even in today's macrocellular networks, handoff call arrivals may not be Poisson for extended periods of time. The average handoff call holding time inside each cell is often non-exponentially distributed. The mean handoff call arrival rates will not remain the same either. Instead, they will change as changes occur in, for example, the number of mobile stations, user mobility pattern, and available services or network configuration.

The limitations of existing methods are primarily caused by a fundamental principle used in these methods: they do not model the resource demands of handoff calls directly; Instead, they model the factors (e.g., handoff call arrival process, call holding time, types of calls, mobility patterns of the users) that impact the demand and then derive the resource demands of future handoff calls from the model of the impacting factors. This leads to two fundamental limitations. First, in a real multimedia wireless IP network, a large number of factors can impact the resource demands of future handoff calls. The set of impacting factors often change over time and the interactions among these factors can be very complex. Consequently, modeling these factors can be prohibitively difficult. Second, to cope with the complexity of modeling the impacting factors, existing methods have to make stringent assumptions on how the impacting factors behave, how they interact with

each other, and how they impact the amount of resources required by handoff calls. Many of these assumptions are not true in real networks, especially not true in multimedia wireless IP networks. For example, almost all existing methods assume that handoff calls arrivals at a cell follow a Poisson process and are stationary in the mean (i.e., the mean arrival rate remains constant over time). In a real network, especially in a network that consists of a large number of small cells, handoff call arrivals are likely to be non-Poisson for extended periods of time. Furthermore, the mean handoff call arrival rate in a real network will typically increase over time as more subscribers are added to the network or as users are becoming more mobile.

Most existing methods also assume that a call will remain active for an exponentially distributed amount of time in each cell the user moves into. This is often not true in real networks. For example, if a user moves at constant speed through several cells, the time the user's call remains active in each cell will be a constant. Third, due to the large number of impacting factors and the complex interactions among them, most existing methods can only estimate the long-term averages of the amount of resources required for handoff calls. Consequently, their estimation often cannot be easily adjusted to respond to the fluctuation of demands.

Furthermore, current approaches to resource reservation reserve radio resources only and make reservation decisions independent of upper layer (e.g., IP layer) resource availability. This could lead to low resource utilization and poor system performance when IP-based base stations are used. For example, current approaches may reserve radio resources for a new call that requires high bandwidth only to determine that the IP-layer does not have sufficient resources to support the call. Meanwhile, the radio resources have been allocated to the high-bandwidth call and could cause a large number of new low-bandwidth calls (which can be

supported at all protocol layers) to be rejected. Furthermore, resource reservation in today's wireless networks is typically performed inside the radio system (e.g., at the radio resource control layer in CDMA networks). This makes it difficult for simultaneous reservation of radio resources and IP-layer resources because lower layer protocols (i.e., radio layer protocols) will have to request resource reservations at higher layers of the protocol stack (i.e., IP layer protocol), which violates basic principles of protocol layering.

Furthermore, existing handoff resource reservation methods are unsuitable for IP-based multimedia wireless networks. First, the amount of bandwidth required to successfully handoff a call in an IP-based multimedia wireless network could be arbitrary (up to the limit of the radio system) and can vary over a wide range. This is especially true when applications/calls can adapt to different levels of service quality and therefore may accept different levels of resources in order to achieve successful handoff as many data or video applications already do. Second, Wireless IP networks are often envisioned to support high-capacity picocells, where handoffs are more frequent than in today's macrocellular networks and handoff demands are likely to be non-stationary for extended periods of time. In fact, even in today's macrocellular networks, handoff call arrivals may not necessarily be a Poisson process but may often be non-stationary for extended periods of time. Third, Wireless IP networks will likely use IP-based wireless base stations – base stations that perform IP-layer processing (e.g., IP packet routing). This suggests that both radio resources (e.g., radio channels) and IP-layer resources (e.g., bandwidth) need to be reserved in a consistent manner for handoff calls.

### SUMMARY

It is therefore an object of the present invention to provide a method for localized dynamic resource reservation in wireless networks that overcome the limitations of the prior art.

5 Our method uses only local information to determine the amount of resources that should be reserved for handoff calls and new calls originating within a cell. Accordingly, a base station employing our method does not have to communicate with other base stations for resource reservation decisions. In this way, base stations can function autonomously as is expected for future IP wireless networks.

10 Our method models and predicts the values of future demands directly. Other methods do not model the resource demands directly. Instead, they model (typically using queuing theories) the factors (e.g., arrival process of handoff calls, call holding times, types of calls) that impact the resource demands, then derive the resource demands from the model of the impacting factors. Modeling the demands directly  
15 enables our method to easily handle any arbitrary call arrival process (including non-Poisson and non-stationary processes), allows calls to require any arbitrary amount of resources, and allows calls to have any arbitrary call holding time distribution in each cell.

20 Our method models the instantaneous values of the resource demands of future handoff and new calls. This enables our method to predict the instantaneous and/or average values of future resource demands. Other existing methods can typically only model and predict average demands. Modeling instantaneous demands enables our approach to respond to demand fluctuations easily and more rapidly than other methods that are based on determining average values.

Our method can be used to determine the future demands and resource reservation levels of any type of calls (e.g., new calls); the method is not limited to handoff calls.

Our method can be used to determine the future demands and resource reservation levels for any type of traffic or service (e.g., video service, voice service, any data service). Our method can also be used to determine the total resource demands and resource reservation levels for multiple traffic or service types without having to estimate the demands for each traffic or service type separately.

Our method can be used to determine the future demands and reservation levels of any type of resource (e.g., radio channels, radio capacity, number of IP addresses, IP-layer capacity). Our method can also be used to determine the total demands and reservation levels of multiple types of resources without having to determine the resource demand and reservation levels of each resource type separately.

Our method can be used to determine the future demands and reservation levels of the resources at any protocol layer (e.g., radio layer resources, IP layer resources). Our method can also be used to determine the total demands and reservation levels of resources at multiple protocol layers without having to determine the resource demand and reservation levels at each individual protocol layer separately..

Our invention reserves radio resources and IP-layer resources automatically. In other words, the proposed method reserves a matching amount of radio resources and IP-layer resources at the same time. The reservation at each layer is committed if and only if sufficient resources at both layers can be reserved. This can increase overall resource utilization and reduce handoff call blocking probability.

Our invention is simple and can therefore be easily implemented in current and future wireless networks. In addition, our method may be implemented in any radio network, including both Time Division Multiple Access (TDMA) and Code Division Multiple Access (CDMA) wireless networks. Finally, our method is applicable regardless of whether handoff is soft or hard.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1A illustrates a prior art cellular network;

FIG. 1B depicts a prior art network executing soft handoff;

FIG. 1C illustrates a future Internet Protocol (IP) based autonomous wireless base station cellular network;

FIG. 2 illustrates multi-layer reservation in accordance with an aspect of our invention;

FIG. 3 is a flow chart of the method steps for multi-layer reservation in accordance with an aspect of invention;

FIG. 4 plots actual and predicted bandwidth requirements for handoff calls as a result of a simulation done in accordance with an aspect of our invention assuming receiving 5 handoff call requests per minute and updating every 10 minutes;

FIG. 5 plots actual and predicted bandwidth requirements for handoff calls as a result of a simulation done in accordance with an aspect of our invention assuming receiving 5 handoff calls per minute and updating every 5minutes;

FIG. 6 plots actual and predicted bandwidth requirements for handoff calls as a result of a simulation done in accordance with an aspect of our invention assuming receiving 2 handoff calls per minute and updating every 10 minutes; and

FIG. 7 plots actual and predicted bandwidth requirements for handoff calls as a result of a simulation done in accordance with an aspect of our invention assuming receiving 2 handoff calls per minute and updating every 5 minutes.

### DETAILED DESCRIPTION

In the discussions to follow we will again refer to different layers of the 7-layer Open System Interconnect (OSI) reference model wherein the layers are ordered as follows: layer 1 is the physical layer and the lowest layer in a stack, layer 2 is the link layer and above layer 1, layer 3 is the network layer and above layer 2, layer 4 is the transport layer and above layer 3, layer 5 is the session layer and above layer 4, layer 6 is the presentation layer and above layer 5, and layer 7 is the applications layer and the highest layer.

Turning to FIG.2 there is illustrated an aspect of our invention that we refer to as Multi-Layer Reservation. As discussed above, prior art approaches to resource reservation reserve radio resources only and make reservation decisions independent of upper layer (e.g., IP layer) resource availability. In addressing this shortcoming of the prior art we move the function of estimating the amount of resource required for calls in a base station 200 from the radio-dependent layers to a software entity referred to as a reservation handler 210 that resides at a radio-independent layer 211 as illustrated in FIG. 2. The reservation handler 210 estimates the resources required to support future calls originating with a cell as illustrated by functional element 220 both for radio-independent and dependent layers 211 and 212, respectively.

Note, the reservation handler 210 may estimate the amount of resources needed for both handoff calls and new calls originating within the base station's cell.

On the other hand, the reservation handler 210 may estimate the amount of



resources needed for either handoff calls or new calls originating within the base station's cell. The choice whether to use both or one type of call is an implementation detail for the discretion of the network operator.

The resource reservation estimate is based on data provided by a handoff and/or new call monitor 230 in the base station radio system. Monitor 230 monitors handoff and/or new call requests, resource requirements, and resource usage as illustrated by functional element 240. The data gathered during a monitoring interval as requested by reservation handler 210, see arrow 248, is directed or provided to the reservation handler 210, see arrow 242. The reservation handler 210 uses the data to estimate the radio dependent and independent resources required to support the handoff and new call requests. Based on the estimate the reservation handler 210 then instructs, arrows 244 and 246, the radio independent and dependent layers 211 and 212, respectively, to reserve these estimated resources for future handoff and new calls.

In accordance with our Multi-Layer Reservation method sufficient resources are reserved at all protocol layers or no resources are reserved at any protocol layer. In addition, our method reduces handoff blocking probability.

The reservation handler 210 estimates or predicts the amount of resources to be reserved based on a stochastic model, such as our model developed below. To overcome accumulating estimation errors over time, the reservation handler 210 will periodically instruct, see arrow 248, the monitor 230 to gather the actual amount of resources used for calls during fixed time periods (for example every  $T_{\text{update}}^0$  minutes). The results will be used by the reservation handler to reset the stochastic model it uses for predicting the amount of resource required for future handoff and new calls.

When the actual amount of resources needed by handoff and/or new calls fluctuate rapidly, periodic measurements by the handoff monitor 230 alone may not be sufficient to capture the changes in the amount of resources needed for future calls. In order to avoid this problem, a significant change in the actual amount of resources requested for calls between two consecutive periodic resource usage measurements triggers the reservation handler 210 to instruct the monitor 230 to collect call resource usage data or information more frequently, i.e.,  $T_{\text{update}} = T_{\text{update}}^0 - \Delta T$ . For example, let  $\Delta r$  represent the difference in resource usage between two consecutive resource usage updates. In addition, let  $R_d$  represent a threshold value. If  $\Delta r \geq R_d$ , the handoff monitor will be triggered to collect resource usage information at shorter time intervals. Thus, the prediction model will be reset more often during unstable periods when the actual resource usage by handoff and/or new calls varies drastically.

When consecutive periodic updates do not fluctuate by a great amount,  $\Delta r < R_d$ , the reservation handler 210 instructs the monitor 230 to collect resource usage information over longer time periods because the system is expected to be in a more stationary state. The reduced frequency of resource usage updates during stable periods avoids unnecessary overhead. The dynamically adjusted frequency of updates during unstable periods enables the prediction model to forecast rapid resource demand changes more accurately.

In FIG. 3 we illustrate the steps of multi-layer reservation in a flow chart. At block 260, handoff and/or and new call arrivals, resource requirements, resource usage are monitored by monitor 230. The data gathered during monitoring is then used to estimate the resources required to support handoff and/or new calls, block 270, by reservation handler 210. The estimate is then used to reserve resources at

all layers, block 280, and to update the monitoring process, block 290, based on the actual resources used. As discussed above, if the difference in resource usage,  $\Delta R$ , is greater than or equal to a threshold value,  $R_d$ , as illustrated at diamond 292, then resource usage monitoring takes place more frequently, block 294. Therefore, if resource usage data was being monitored, and forwarded to block 270 for estimating, at a rate of  $T_{update}^0$ , then the update rate is increased by  $\Delta T$ . Consequently, resources are reserved more frequently at block 280 by reservation handler 210 communicating with the radio independent and dependent layers 211 and 212.

On the other hand, if the difference in resource usage is less than  $R_d$ , then the resource usage monitoring is done less frequently, for example at rate  $T_{update}^0$ , as is illustrated at block 296.

Note our method is readily applicable in wireless networks that employ either soft or hard handoff.

We will now turn to another aspect of our invention that improves on the prior art and our Multi-Layer Reservation method described above. As discussed above, prior art methods that use only location information to estimate future resource reservation model the factors (e.g., arrival process of handoff calls, call holding times, types of calls) that impact the resource demands, then derive the resource demands from the model of the impacting factors. We propose a new resource prediction and reservation method that overcomes the limitations of existing methods by using Wiener estimation-based stochastic models to directly model the instantaneous amount of resources needed for handoff calls.

We model the total amount of resources,  $R(t)$ , required to support handoff and/or new calls in a cell at time  $t$  as a stochastic process.  $R(t)$  can represent, for example, the number of radio channels, the amount of bandwidth, or the number of IP addresses required to support calls. The idea is to use the current and past values of  $R(t)$  to predict the future values of  $R(t)$ . Since the current and past values of  $R(t)$  can be measured by a base station locally without exchanging any information with other base stations, estimating the future values of  $R(t)$  can be carried out using only local information.

We use Wiener process-based stochastic models to model  $R(t)$ . A Wiener process is a Markov process where only the present value is relevant for predicting the future. It has been successfully used to model stochastic processes where the value of a random variable is affected by a large number of factors, each with a small impact. For example, the Wiener process has been used in physics to model the motion of a particle that is subject to a large number of small molecular shocks (which is sometimes referred to as Brownian motion). It has also been widely used to model the behavior of stock prices. The amount of resources required to support handoff and new calls share many similar properties with Brownian motion and stock prices – it is a random variable whose value changes over time and the change is impacted by a large number of factors, each with a small impact. For example, such factors include, sizes of the cells, the number of mobile stations in each cell, speed and mobility pattern of each mobile station, types of services supported by the cells, type and number of services used by each mobile station at any given time, etc. These characteristics suggest that the Wiener process could be an effective way to model  $R(t)$ .

Let  $\Delta t$  be the prediction time interval. Using the basic Wiener process,  $R(t)$  can be modeled as in Equation (1).

$$\Delta R = R(t) - R(t - \Delta t) = \alpha \sqrt{\Delta t} \quad (1)$$

where  $\alpha$  is a random value drawn from a standard normal distribution (i.e., a normal distribution with a mean of zero and a standard deviation of 1.0). The basic Wiener model in Equation (1) has the following main properties, which hold regardless of the value of  $\Delta t$ :

1. the value of  $\Delta R$  for any given time interval  $\Delta t$  is independent of the starting time of  $\Delta t$ ,
2. the values of  $\Delta R$  for any two different time intervals  $\Delta t_1$  and  $\Delta t_2$  are independent, and
3. the mean and standard deviation of  $\Delta R$  are 0 and  $\sqrt{\Delta t}$ , respectively.

Many variations of the basic Wiener model exist and may be used to model more complex resource demand processes. For example, the model in Equation (2) allows the mean and the standard deviation of  $\Delta R$  to change over time.

$$\Delta R = \mu \Delta t + \alpha \delta \sqrt{\Delta t} \quad (2)$$

where  $\mu$  is a constant referred to as the expected change rate of  $\Delta R$  and  $\delta$  is a constant referred to as the standard deviation rate of  $\Delta R$ .  $\Delta R$ , as expressed in Equation (2), is a normally distributed random variable with mean  $\mu \Delta t$  and standard deviation  $\delta \sqrt{\Delta t}$ . Those of ordinary skill in the art will note that other variations of the Weiner model may also be used.

For any given time interval  $\tau$ ,  $\mu$  and  $\delta$  can be estimated using any statistical estimation techniques. For example,  $\mu$  and  $\delta$  can be estimated based on the mean and the variance of the sample values of  $\Delta R$  in previous time intervals of length  $\tau$ . A sample value of  $\Delta R$  can be a measured actual value or a predicted value of  $\Delta R$ . Let  $t$  be the current time, then  $\mu$  and  $\delta$  can be estimated by setting  $\mu\tau$  and  $\delta\sqrt{\tau}$  to the mean and standard deviation, respectively, of the sample values of  $\Delta R$  in the previous  $k$  time intervals:  $[t, t-\tau]$ ,  $[t-\tau, t-2\tau]$ , ...,  $[t-(k-1)\tau, t-k\tau]$ . Let  $r(x)$  be the sample value of  $R(x)$ , the sample value of  $\Delta R$  in time interval  $[t-i\tau, t-i\tau-\tau]$  will be  $r(t-i\tau)-r(t-i\tau-\tau)$ ,  $i=0, \dots, k-1$ . The estimated value  $\hat{\mu}$  of  $\mu$  will be given by Equation (3).

$$\hat{\mu} = \frac{\sum_{i=0}^{k-1} (r(t-i\tau) - r(t-i\tau-\tau))}{k\tau} = \frac{r(t) - r(t-k\tau)}{k\tau} \quad (3)$$

The estimated value  $\hat{\delta}$  of  $\delta$  will be given by Equation (4).

$$\hat{\delta} = \frac{1}{\sqrt{\tau}} \sqrt{\frac{\sum_{i=0}^{k-1} (r(t-i\tau) - r(t-i\tau-\tau) - \hat{\mu}\tau)^2}{k}} \quad (4)$$

Since  $\Delta R$  is normally distributed, we should achieve satisfactory estimates of  $\mu$  and  $\delta$  if  $k$  is 25 or larger.

The sampling time interval  $\tau$  for estimating  $\mu$  and  $\delta$  does not have to be the same as the prediction time interval  $\Delta t$  used by a base station to predict future resource demands. To reduce sample collection time, accurate estimates of  $\mu$  and  $\delta$  can be obtained using samples of  $\Delta R$  taken more frequently than one sample in each prediction time interval. Suppose, for example, that resource prediction is performed every  $\Delta t = 10$  minutes, but the actual resource demand levels are

sampled every  $\tau=1$  minute. Then,  $\mu$  and  $\delta$  can be estimated using the 25 sample values of  $\Delta R$ , each taken in one of the past 25 minutes, rather than the sample values of  $\Delta R$ , each taken in one of the last 25 prediction time intervals. As a result,  $\mu$  and  $\delta$  can be estimated using the samples of  $\Delta R$  taken during a 25-minute time window rather than a 250-minute time window.

Suppose that a base station knows the value of  $R(t)$ , the amount of resources required for all handoff calls at time  $t$ . The amount of additional resource  $\Delta R$  required at a future time  $t + \Delta t$  (or over a future time period  $\Delta t$ ) for handoff calls can be predicted based on  $R(t)$  and the predicted values of  $\Delta R$  for the time interval  $\Delta t$ . Any point or interval predictions of  $\Delta R$  may be used. Using Equation (2), an unbiased minimum variance estimate of  $\Delta R$  is  $\hat{\mu}\Delta t$ . The point value generated directly by Equation (2) can also be used as a point prediction of  $\Delta R$ . Accuracy of the point estimate depends on  $\delta$  and the prediction time interval  $\Delta t$ . To provide a confidence level in the estimates, we can use interval prediction. The confidence level for a predicted interval (i.e., a confidence interval) of  $\Delta R$  is the probability that the actual demand falls inside the predicted interval. Since  $\Delta R$  is modeled as a normal random variable for any given prediction time interval  $\Delta t$ , the confidence interval for any given confidence level can be determined easily based on  $\hat{\mu}$  and  $\hat{\delta}$ .

Interval prediction allows us to predict the worst-case dropping probability  $P$  of handoff calls. In particular, we can determine a level  $L$  such that  $\text{Prob}(\Delta R \leq L) = 1 - P$ . This level  $L$  is called a  $(1-P)*100\%$  upper confidence bound for  $\Delta R$ . If this level  $L$  is used to set resource reservation levels, we have a statistical guarantee that the handoff dropping probability in the next time interval  $\Delta t$  is  $P$ .

A base station can learn the current and past value of  $R(t)$  by monitoring the amount of resources requested by handoff and/or new calls during an initial period of time. The initial value is then used in the Wiener model to predict future demands. The predicted demand at any time  $t$  may also be used to predict future demands.

The use of Wiener process models enables our method to model and predict the instantaneous values of the resource requirements of future handoff calls directly. As such, our method can easily handle any arbitrary handoff call arrival process (including non-Poisson and non-stationary processes) and allows calls to require any arbitrary amount of resources and to have any arbitrary call holding time distribution in each cell a user travels into. These capabilities can not be achieved by prior art methods. Moreover, modeling instantaneous demands enables our approach to respond to demand fluctuations more rapidly than prior art methods by dynamically changing the values of the parameters in our model and by increasing or decreasing the rate at which the predictions are generated and resources are reserved; this is shown as block 290 in FIG. 3. Furthermore, because each base station records the actual amount of resource required for handoff calls periodically or as triggered by significant events (as explained above) and uses the actual values to reset the prediction model, prediction error does not accumulate significantly over time.

In an effort to determine the effectiveness of our method in reserving the total amount of bandwidth required to support handoff calls of multiple service types we performed a numerical analysis (via simulations) of our method. We will now describe the results of those simulations.

In simulating our method we assume handoff call arrivals to be Poisson (because a Poisson process is simpler and requires less computational resources).



We considered two mean handoff call arrival rates:  $\lambda = 5$  and 2 handoff calls per minute. For both handoff call arrival rates, the amount of bandwidth needed to successfully handoff a call is assumed to be between 16 kbps and 56 kbps. We also assume that in each minute there is a 10% probability that a very high bandwidth call is handed off into the cell. We assume that each handoff call remains active in the cell for an exponentially distributed holding time with an average time of 10 minutes. For the actual handoff call bandwidth usage, we created two sets of simulated values, one for each  $\lambda$  value. For each mean handoff call arrival rate, we simulated handoff arrival rates, call holding times and call bandwidth requirements using random number generators with the appropriate distributions and mean values. We then used MATLAB to implement our prediction model based on Equation (3) and to determine the predicted bandwidth requirements for handoff calls.

The above assumptions on handoff arrival rates, call holding times and call bandwidth needs can represent, for example, the following scenario in a real network. The network supports voice services at about 16 kbps, Internet access services at a number of data rates ranging from 16 kbps to 56 kbps, and a real-time video service at 384 kbps. Furthermore, the majority of mobile calls are calls for Internet access and a small percentage of users use video service.

FIG. 4 shows the simulated actual bandwidth usage for all handoff calls in the cell (including any on-going call that is in the cell because of a handoff) and the predicted values. FIG. 4 assumes that  $\lambda = 5$  handoffs per minute. The prediction is performed once every minute, i.e.,  $\Delta t = 1$  minute. The update interval  $T_{\text{update}}$  is assumed to be 10 minutes. In other words, starting from time  $t = 0$ , the resource requirements for the next minute will be predicted based on either the actual or the predicted demands for handoff calls during the current minute.

Furthermore, once every ten minutes, the base value for the prediction model is reset to the simulated actual bandwidth requirements of the handoff calls. The actual demands in this case happens to be stationary in the mean after the initial system startup time period. Therefore, the means of  $R(t)$  and  $R(t+\Delta t)$  should be the same for any  $t$  and  $\Delta t$ , which means that  $\mu$  in Equation (2) can be set to zero. The average percentage difference between the predicted values and the simulated values is  $22.4\% \pm 19.6\%$ . FIG. 5 shows the actual 410 and the predicted 420 amount of bandwidth required for handoff calls when we shorten the update interval to 5 minutes while leaving all other parameters unchanged. In this case, the percentage average difference between the predicted and the simulated values reduces to  $13.5\% \pm 13.8\%$ .

FIG. 6 and FIG. 7 show the actual and the predicted bandwidth requirements for handoff calls when  $\lambda = 2$  handoffs per minute. FIG. 6 assumes that  $T_{\text{update}}$  is equal to 10 minutes and FIG. 6 assumes  $T_{\text{update}}$  is equal to 5 minutes. In both FIGS. 6 and 7,  $\mu=0$  and  $\Delta t = 1$  minute. When  $T_{\text{update}}=10$  minutes, the average percentage difference between the predicted values and the simulated values is  $24.7\% \pm 22.6\%$ . When the update interval is 5 minutes, the percentage difference is on average  $16.7\% \pm 16.7\%$ . The average percentage difference is higher in the cases reported here when  $\lambda$  drops to 2 handoffs per minute. This is because too few handoff calls occur when  $\lambda = 2$  handoffs per minutes, but the bandwidth required for each handoff call continues to vary over a wide range and the probability of very high bandwidth requirements remains the same. Consequently, the handoff traffic becomes more bursty. Despite the increased burstiness, our reservation method continues to performs reasonably well.

Our simulations show that when the average handoff arrival rate and/or the traffic holding time increases, the handoff resource usage becomes smoother. In such cases, our method can generate close predictions for a longer time. Therefore, the prediction model can be reset less frequently than when the handoff bandwidth demands are more bursty. In general, the update interval  $T_{\text{update}}$  can be varied to capture the burstiness of traffic. The value of  $T_{\text{update}}$  can be changed using the triggering mechanism described above.

Note that results from earlier investigations would have incorrectly estimated the bandwidth values by a larger amount since they were based on average values. When the network must handle calls that may require high bandwidth for relatively short periods of time, the bursty nature of the bandwidth requirements can not be effectively captured with average values. For example, for the set of simulated values used in FIG. 4 when  $\lambda=5$  handoffs per minute, the average handoff call bandwidth requirement would be about 2128.7 kbps. If this value was used to reserve resources, then the percentage difference between the actual and the reserved values would be about 33% with a standard deviation of about 84%. For the set of simulated values determined when  $\lambda = 2$  handoffs per minute, the average bandwidth required for handoff calls would be about 955.2 kbps and the average percentage difference increases to approximately 60%.

The above description has been presented only to illustrate and describe the invention. It is not intended to be exhaustive or to limit the invention to any precise form disclosed. Many modifications and variations are possible in light of the above teaching. The applications described were chosen and described in order to best explain the principles of the invention and its practical application to enable others

skilled in the art to best utilize the invention on various applications and with various modifications as are suited to the particular use contemplated.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228  
2229  
2230  
2231